



## NAC3MPA-1

Successor product: NAC3MPXXA

Chassis connector, power-in, 3/16" flat tab terminals, blue

The powerCON is a locking 3 conductor equipment AC connector with contacts for line, neutral and pre-mating ground contact. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

**Attention:** The powerCON is a connector without breaking capacity, i.e. the powerCON should not be connected or disconnected under load or live!

### Features & Benefits

- |   |   |
|---|---|
| <ul style="list-style-type: none"><li>• Locking 20 A / 250 V ac appliance coupler</li></ul>   | <ul style="list-style-type: none"><li>• 3 contacts for line, neutral and pre-mating safety ground</li></ul> |
| <ul style="list-style-type: none"><li>• Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating</li></ul> | <ul style="list-style-type: none"><li>• Fast and easy twist lock latching system</li></ul>                  |
| <ul style="list-style-type: none"><li>• Extremely robust and reliable</li></ul>   | <ul style="list-style-type: none"><li>• Ergonomic design</li></ul>  |
| <ul style="list-style-type: none"><li>• User friendly latch design for easy handling</li></ul>  | <ul style="list-style-type: none"><li>• UL, cUL recognized components<br/>VDE certified</li></ul>           |

## Technical Information

Product	
Title	NAC3MPA-1
Gender	male

Electrical	
Contact resistance	$\leq 3 \text{ m}\Omega$
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	$> 0.1 \text{ G}\Omega$ (after damp heat test IEC 68-2-30)
Number of electrical contacts	2 + PE
Rating Europe	EN 61984:20 A 250 V AC
Rating USA	UL 1977:20 A 250 V AC

Mechanical	
Lifetime	$> 1000$ mating cycles
Wiresize	
Locking device	Quick Lock
Mounting direction	Front mounting
Chassis shape	D

Material	
Contact plating	2 $\mu\text{m}$ Ag
Locking element	Steel Ck67
Shell	Polyamide (PA 6.6 30 % GR)
Contacts	Bronze (CuNi1Si0.2)

Environmental	
Flammability	UL 94 V-0
Protection class	IP 20
Temperature range	-30 °C to +80 °C