



## NAC3FXXA-W-S

IEC EN 60320-1 compliant | Accepted for cord sets  
as per IEC EN 60799:2021

Locking AC mains cable connector, keyed and color  
coded (blue) for power-in, screw terminal assembly,  
for cable diameters 6 - 12 mm.

The powerCON FXXA/FXXB is a single phase (3  
conductor) lockable power connector with Circuit  
Breaking Capability when mated with powerCON XX  
Series receptacles.

It replaces appliance couplers wherever a very  
rugged solution in combination with a locking  
device is needed to guarantee a safe power  
connection.



## Features & Benefits

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• IEC EN 60320-1 / UL 60320-1 / CSA C22.2 No. 60320-1 certified, thus accepted as a component for cord sets acc. to IEC 60799 / UL 817 and equipment acc. to IEC 62368-1</li></ul> | <ul style="list-style-type: none"><li>• Ergonomic design with slip-proof two-component molded housing</li></ul>                      |
| <ul style="list-style-type: none"><li>• Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating</li></ul>  | <ul style="list-style-type: none"><li>• Unique NEUTRIK locking bushing and strain relief for cable diameters 6 mm to 12 mm</li></ul> |
| <ul style="list-style-type: none"><li>• Easy to assemble because the strain relief locks with the insert mechanically and aligns with the housing</li></ul>  | <ul style="list-style-type: none"><li>• Superior NEUTRIK quality standard, extremely robust and reliable</li></ul>                   |
| <ul style="list-style-type: none"><li>• Easy and reliable twist lock system</li></ul>  | <ul style="list-style-type: none"><li>• Improved kink protection by two-component bushing</li></ul>                                  |

## Assembly instruction video for powerCON FXXA/FXXB

Cable list

Cable: IEC/EN 60320-1		3 x 1.5 mm <sup>2</sup>	3 x 2.5 mm <sup>2</sup>			
■ H07RN-F		-S	-L			
■ H05RN-F		-S	-			
■ H05VV-F		-S	-S			
Cable: UL 60320-1, CAN/CSA-C22.2 No. 60320-1				16/3 AWG	14/3 AWG	12/3 AWG
■ SOOW				-S	-L	-L
■ SJOOW				-S	-S	-L
■ SJTOOW				-S	-S	-S

## Technical Information

Product	
Title	NAC3FXXA-W-S
Connector series	powerCON blue/grey

Electrical	
Contact resistance	$\leq 2 \text{ m}\Omega$
Dielectric strength	$> 3 \text{ kVac}$ (after mating cycles)
Insulation resistance	$> 10 \text{ G}\Omega$ (initially)
Number of electrical contacts	2 + PE
Rating Europe	EN 60320-1: 16 A 250 V AC, CBC
Rating USA / Canada	cUL 60320-1: 20 A 127 V AC, CBC

Mechanical	
Cable O.D.	6 - 12 mm
Lifetime	Typically 5'000 mating cycles
Wiresize (mm <sup>2</sup> )	1.5 – 2.5 mm <sup>2</sup>
Wiresize (AWG)	16 – 12 AWG
Locking device	Twist lock
Termination	Screw type terminals

Material	
Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

Environmental	
Temperature range	-33 °C to +80 °C
Protection class	IP20
Flammability acc. to UL94	V-0